

# Litaflex-Glue 600



## Technical Information

<b>Application:</b>	Litaflex glue 600 is specially suitable for a moisture resistant fixing of Litaflex on a non soaking ground. It is also suitable for an elastic coating of alufoil to the non-combustible foam Litaflex.
<b>Properties:</b>	Beige liquid non-combustible, free of organic solvents, brushable and sprayable, mixable with water. Resistant against temperatures up to 800°C. Resistant to moisture after complete drying.
<b>Instructions for processing:</b>	<p>The provided background must be clean and free from dust, rust, oil and grease.</p> <p>Stir well before processing. One side coating by brush or roller on the non-soaking side. Join together and compress immediately after joining.</p> <p>Surface drying: 5 - 10 minutes, Complete drying: 6 - 8 hours To shorten up drying heating up to max.100°C is possible.</p> <p>Required quantity : 50 - 150 g/m<sup>2</sup>, depending on absorptive capacity of background.</p>
<b>Storage:</b>	<p>Litaflex-glue 600 has to be stored free of frost.</p> <p>Stability approx. 6 months.</p> <p>Dangerous materials class acc. to VbF: none (not flammable)</p>
<b>Lots:</b>	Containers of 2,5 kg, 7,5 kg, 15 kg and 25 kg.

Information, details, and data of our brochure are according to the best of our knowledge, if possible proved by test and are for information only. We recommend tests according to your specific conditions. Be assured that our technical and commercial department will be at your service at all times.

10/2023